


ACIER INOXYDABLE AUSTENITIQUE 304L CALIBRE A FROID ROND



ETAT
- Etiré à froid
- Tourné galeté

Code article

EXEMPLE DE COMMANDE **304LETR20**

Code article	d (mm)	Poids (kg / m)	Tolérances	
			ISO	μ
304LETR3	3	0,055	h 10	$\begin{matrix} 0 \\ -40 \end{matrix}$
304LETR4	4	0,099	h 10	$\begin{matrix} 0 \\ -48 \end{matrix}$
304LETR5	5	0,154	h 10	$\begin{matrix} 0 \\ -48 \end{matrix}$
304LETR6	6	0,222	h 10	$\begin{matrix} 0 \\ -48 \end{matrix}$
304LETR7	7	0,302	h 10	$\begin{matrix} 0 \\ -58 \end{matrix}$
304LETR8	8	0,395	h 10	$\begin{matrix} 0 \\ -58 \end{matrix}$
304LETR9	9	0,499	h 10	$\begin{matrix} 0 \\ -58 \end{matrix}$
304LETR10	10	0,617	h 10	$\begin{matrix} 0 \\ -58 \end{matrix}$
304LETR11	11	0,746	h 10	$\begin{matrix} 0 \\ -70 \end{matrix}$
304LETR12	12	0,888	h 10	$\begin{matrix} 0 \\ -70 \end{matrix}$
304LETR13	13	1,042	h 10	$\begin{matrix} 0 \\ -70 \end{matrix}$
304LETR14	14	1,208	h 10	$\begin{matrix} 0 \\ -70 \end{matrix}$
304LETR15	15	1,387	h 10	$\begin{matrix} 0 \\ -70 \end{matrix}$

Code article	d (mm)	Poids (kg / m)	Tolérances	
			ISO	μ
304LETR16	16	1,578	h 10	$\begin{matrix} 0 \\ -70 \end{matrix}$
304LETR17	17	1,782	h 10	$\begin{matrix} 0 \\ -70 \end{matrix}$
304LETR18	18	1,998	h 10	$\begin{matrix} 0 \\ -70 \end{matrix}$
304LETR19	19	2,226	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR20	20	2,466	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR21	21	2,719	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR22	22	2,984	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR23	23	3,262	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR24	24	3,551	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR25	25	3,853	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR26	26	4,168	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR27	27	4,495	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR28	28	4,834	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$

Code article	d (mm)	Poids (kg / m)	Tolérances	
			ISO	μ
304LETR30	30	5,549	h 10	$\begin{matrix} 0 \\ -84 \end{matrix}$
304LETR32	32	6,313	h 10	$\begin{matrix} 0 \\ -100 \end{matrix}$
304LETR35	35	7,553	h 10	$\begin{matrix} 0 \\ -100 \end{matrix}$
304LETR36	36	7,990	h 10	$\begin{matrix} 0 \\ -100 \end{matrix}$
304LETR38	38	8,903	h 10	$\begin{matrix} 0 \\ -100 \end{matrix}$
304LETR40	40	9,865	h 10	$\begin{matrix} 0 \\ -100 \end{matrix}$
304LETR42	42	10,876	h 10	$\begin{matrix} 0 \\ -100 \end{matrix}$
304LETR45	45	12,485	h 10	$\begin{matrix} 0 \\ -100 \end{matrix}$
304LETR50	50	15,413	h 10	$\begin{matrix} 0 \\ -100 \end{matrix}$
304LETR55	55	18,650	h 10	$\begin{matrix} 0 \\ -120 \end{matrix}$
304LETR60	60	22,195	h 10	$\begin{matrix} 0 \\ -120 \end{matrix}$