



ACIER DE CONSTRUCTION NON ALLIE A37 ETIRE A FROID HEXAGONE



Code article	s (mm)	Poids (kg / m)	Tolérances	
			ISO	μ
A37ETH7	7	0,333	h 11	⁰ ₋₉₀
A37ETH8	8	0,435	h 11	⁰ ₋₉₀
A37ETH9	9	0,551	h 11	⁰ ₋₉₀
A37ETH10	10	0,680	h 11	⁰ ₋₉₀
A37ETH12	12	1,130	h 11	⁰ ₋₁₁₀
A37ETH13	13	1,149	h 11	⁰ ₋₁₁₀
A37ETH14	14	1,332	h 11	⁰ ₋₁₁₀
A37ETH15	15	1,530	h 11	⁰ ₋₁₁₀
A37ETH16	16	1,740	h 11	⁰ ₋₁₁₀
A37ETH17	17	1,965	h 11	⁰ ₋₁₁₀
A37ETH18	18	2,203	h 11	⁰ ₋₁₁₀
A37ETH19	19	2,454	h 11	⁰ ₋₁₃₀
A37ETH20	20	2,719	h 11	⁰ ₋₁₃₀

Code article	s (mm)	Poids (kg / m)	Tolérances	
			ISO	μ
A37ETH21	21	2,998	h 11	⁰ ₋₁₃₀
A37ETH22	22	3,290	h 11	⁰ ₋₁₃₀
A37ETH23	23	3,596	h 11	⁰ ₋₁₃₀
A37ETH24	24	3,916	h 11	⁰ ₋₁₃₀
A37ETH25	25	4,249	h 11	⁰ ₋₁₃₀
A37ETH26	26	4,596	h 11	⁰ ₋₁₃₀
A37ETH27	27	4,956	h 11	⁰ ₋₁₃₀
A37ETH28	28	5,330	h 11	⁰ ₋₁₃₀
A37ETH30	30	6,118	h 11	⁰ ₋₁₃₀
A37ETH32	32	6,961	h 11	⁰ ₋₁₆₀
A37ETH35	35	8,328	h 11	⁰ ₋₁₆₀
A37ETH36	36	8,810	h 11	⁰ ₋₁₆₀
A37ETH38	38	9,816	h 11	⁰ ₋₁₆₀

EXEMPLE DE COMMANDE Code article
A37ETH10

Code article	s (mm)	Poids (kg / m)	Tolérances	
			ISO	μ
A37ETH40	40	10,88	h 11	⁰ ₋₁₆₀
A37ETH41	41	11,43	h 11	⁰ ₋₁₆₀
A37ETH42	42	11,99	h 11	⁰ ₋₁₆₀
A37ETH45	45	13,77	h 11	⁰ ₋₁₆₀
A37ETH46	46	14,38	h 11	⁰ ₋₁₆₀
A37ETH50	50	16,99	h 11	⁰ ₋₁₆₀
A37ETH55	55	20,56	h 11	⁰ ₋₁₉₀
A37ETH60	60	24,47	h 11	⁰ ₋₁₉₀
A37ETH65	65	28,72	h 11	⁰ ₋₁₉₀
A37ETH70	70	33,31	h 11	⁰ ₋₁₉₀
A37ETH80	80	43,51	h 11	⁰ ₋₁₉₀